

BXR-150 Box Phone



- Usually mounted in elevator phone cabinet.
- Activated by pressing call button on front of unit.
- LED flashes to indicate that call has been answered.
- Dimensions: 8.5" high x 5.25" wide x 2.33" deep.
- BXR-150B: Includes bilingual lettering (English / French), manuals and installation instructions in both languages.

WEBBPHONE OPERATION

The Webbphone is an AC-powered emergency handsfree telephone. It has a rechargeable NiCad backup battery, connects to a regular phone line and is ADA compliant.

Pushing the help button activates the Webbphone. It will then automatically call a pre-programmed number for assistance. Should this primary number be busy or not answered, the unit will call a second location for assistance. When the call is answered, a location announcement message will tell the operator exactly where the call is coming from.

For callers with a hearing disability, an LED will also begin flashing to alert them that their call has been received.

It is also possible to call into the Webbphones through the telephone system. All units connected to the telephone line being called will ring and then turn on. The caller will then hear a voice message instructing them on how to select the particular cab they wish to speak to.

Leading-edge technology provides all Webbphones with the ability to check their own operation. Our exclusive Auto-Chek™ feature will automatically inform the building owner if any of their units are not working normally. This powerful feature provides unparalleled safety and assurance for both passengers and building owners.

Other Major Features:

- Up to 6 units may share the same telephone line. With an LS-250 Rescue Station system installed, up to 80 units may share the same telephone line.
- Adjustable talk time (1 – 99 minutes). Operator can extend the length of a conversation as long as they wish.
- Excellent voice quality.
- Compatible with SoundNet monitoring protocol, ringdown equipment and PBX switchboards.
- Unique SmartCall™ technology allows more than one elevator to be using the system at the same time.
- Password protection for secure remote programming and non-volatile memory for all functions.
- Built in keypad and voice prompts make the Webbphone the easiest handsfree telephone to program.

Note:

Further operational details of the Webb phone may be found in the User Manual.

Applications:

Elevators, Area of Rescue stations, parkades, hospitals, senior citizen homes, building entrances, campus emergency stations, mall security, reservation desks, ATM machines, roadside emergency stations, all security environments.

BXR-150 Box Phone

SPECIFICATIONS

Description:	Box style handsfree telephone. Surface mounted.
Elevator Wiring Requirements:	One shielded, twisted-pair communication cable. Shield should be grounded at controller end of traveling cable.
Phone line Requirements:	Standard analog loop start voice grade telephone line or PBX
AC/DC Transformer (supplied):	120V AC, 60 Hz input / 9V DC, 500 mA output
Backup Power:	9V NiCad rechargeable battery. Normal lifetime is 5 yrs.
Maximum number of units:	6 sharing same phone line
On-hook Phone Line Voltage:	24V – 55V (nominal 48V DC)
Off-hook Phone Line Voltage:	3V – 10V (nominal 6V DC)
Off-hook Loop Current:	25 mA – 35 mA (nominal 30 mA)
Ringling Voltage:	40 – 130V AC
LED (red):	Operating voltage 1.7V – 2.1V. Operating current 10 – 25 mA.
Microphone:	Unidirectional electret condenser. Frequency range 100hz – 12 KHz.
Operating Range:	0 – 60 degrees Centigrade
Ringer Equivalence (REN):	0.8 USA 0.3 Canada
Certification:	ADA compliant. FCC Part 68 registered. Industry Canada registered.
Dimensions:	5.25" (133 mm) wide x 8.5" (216 mm) high x 2.375" (60 mm) deep.
Finish:	18 gauge steel with black powder coating and white silkscreen lettering.
Shipping Weight:	3.8 lb (1.7 kg.)



Canada: *Head Office:* 4427 Dawson Street, Burnaby BC V5C 4B8 • Tel: 604.502.9007 • Fax: 604.502.9044
Calgary AB, Toronto ON, Montreal QC

USA: Bellingham WA

Toll Free: 1-877-731-1010 • **Inquiries:** info@webbelectronicsinc.com • **Website:** www.webbelectronicsinc.com