



WEBB DISPLAY KIT WDK-302 (7", 10", 12") COMMERCIAL TWO-WAY VIDEO PLAYER KIT (A17.1 AND B44 2019)

FEATURES AND BENEFITS



WEBB DISPLAY KIT: WDK-12

- HD Resolution
- Frameless design for flexible installation environments
- Clearly audible voice reproduction
- Integrates seamlessly into the WebbSafe-300 System
- Comes complete with Webb Media Player to accommodate Two-Way Audio Video
- 1080p Camera included
- ASME 17.1, B44-2019 and Compliant. Also IBS 2018 compliant.
- Portrait or Landscape mode

Description: The WDK-302 Frameless monitor is designed for commercial installation behind a custom enclosure like a display wall or COP in an elevator. Designed to function with the WebbSafe - 300™ system can be used for electronic bulletin boards, video displays or two way audio and video real-time communication.

Ordering Information

WDK-7	7" Display Unit, w/media player, camera and emergency phone
WDK-10	10" Display Unit, w/media player, camera and emergency phone
WDK-12	12" Display Unit w/media player, camera and emergency phone
WDK-15	15" Display Unit w/media player, camera and emergency phone



TYPICAL APPLICATIONS

Areas of Rescue
Parkades
Emergency Stations
Hospitals
Building Entrances
Reservation Desks
Mall Security
Retirement Homes



WDK-302 COMMERCIAL GRADE TWO-WAY VIDEO PLAYER KIT (A17.1 AND B44 2019)

Specification:

Screen Size:	7", 10", 12" or 15" Diagonal
Display Resolution (px)	720p or 1080p
Contrast Ratio:	500:1 (typ.)
Display Color:	16.2M (6bit + FRC)5
Brightness:	(CD/m ²) 250 (typ.)
Viewing Angles:	(CR >= 10) -65~65 (H); -55~65 (V)
Touch Screen:	PCAP
Signal Connector:	15 pin D-sub
Power Source:	AC 100~240 V, Universal, ±10%
Power Consumption:	25 W typical, normal operation, 12VDC 2A, or POE power
Power Management:	VESA DPMS Compliant
Plug & Play:	VESA DDC 1/2B
Input:	HDMI
Range:	Horizontal / Vertical 31.5~60kHz / 60~75kHz
Phone:	Built-in digital IP Phone for two-way audio communication. SIP compliant
Speaker	8 Ohm, 0.25 Watt, 300Hz - 5kHz
Mic	Unidirectional electric condenser, 100Hz - 12kHz
Camera	1080P, WDR, 120 degree camera
SD Card:	Micro-SD slot
Operating Temperature:	0 - 60°C
Certification/ Compliance:	ADA, FCC - Part 68, Industry Canada, ASME A17.1, CSA B44 -2019
Warranty:	2 years from date of purchase